DINI ARGEO
Scales - Weighing systems

DFWATEX

DFW "ATEX2GD": WEIGHT INDICATOR FOR ATEX 1 & 21 ZONES



Weight indicator for areas classified as hazardous with protection methods according to:
ATEX II 2(2)G Ex ib [ib Gb] IIC T4 Gb for gases,
ATEX II 2(2)D Ex tb [ib Db] IIIC T197°C IP65 Db for dust.
Ideal for creating weighing systems, batching, and automation systems. EC-Type-Examination certificate according to Annex III (ATEX directive). CE-M approvable (OIML R-76 / EN 45501).

Working in cooperation with:

UAB DESKA
PRAMONES 5 - LT-94102 - KLAIPEDA - LITHUANIA
Tel. 00370-46-381089 Fax. 00370-445-76466
info@deska.lt

The best solution for advanced industrial applications

MAIN FEATURES

- Waterproof 17-key numerical and functional keyboard.
- LCD display with 6 25-mm high contrast digits, clearly visible even in poor lighting conditions and with low temperatures, and with 6 LEDs for showing the active functions.
- Satined IP68 stainless steel case.
- Dimensions 264x174x115mm.
- Suitable for use on the table, or wall.
- Up to 10.000e or multirange 3 x 3000e @ 0,3 µV/d in CE-M approved version for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- Up to 8 signal linearization points with DINITOOLS (3 from keypad).
- A/D 24-bit sigma-delta conversion, up to 200 conv./sec. autoselect.
- Digital calibration and set-up from keyboard; Instrument management & configuration from PC with DINITOOLS.
- Power supply through external module: with optional battery pack; or with optional power adapter connectable to mains at 230 Vac or at 24 Vdc.
- Connection with up to 4 load cells having 350 Ohm input resistance.

FUNCTIONS

- SCALE FUNCTIONS
  -Zeroing
  - Automatic Tare
  - Presettable Tare
  - ID1 and ID2 10-digit Codes
  - Print and data transmission commands
  - selectable function command
  - on/off switching.
- SELECTABLE FUNCTIONING MODES
  - High Resolution Weighing x 10
  -Net/Gross or lb/kg conversion
  - Accumulation
  - Formula weighing
  - +/- Checkweighing
  - Counting (Max. resolution of 1.500.000 divisions).
  - In/Out Truck weighing
  - Hold
  - Peer-to-peer (up to 4 remote connectable indicators).
  - Set Point Control (only in the DFWATEX2GDIO version combined with PW200XRDxxx and PW200IO options).
  - MODBUS serial protocol.

I/O SECTION (ONLY WITH THE DFWATEX2GDIO MODEL):

- Fiber optic bidirectional port for connection with printer, labeller, PC, or PLC in safe area.
- 4 logic inputs and 4 barriered digital outputs, connectable to other intrinsic safety devices in a hazardous area (only with the DFWATEX2GDIO version combined with PW200XRDxxx and PW200IO options).

www.diniargeo.com



DINI ARGEO FRANCE sarl
Nogent-sur-Marne

DINI ARGEO GMBH
Sinsheim - Germany

DINI ARGEO UK Ltd
Taunton - United Kingdom

DINI ARGEO WEIGHING INSTRUMENTS Ltd
Shanghai - China

DINI ARGEO WEIGHBRIDGES
Calto (RO) – Italy

DINI ARGEO
Scales - Weighing systems

HEAD OFFICE
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy

ATEX

ISO 9001:2008

UAB DESKA

PRAMONES 5 - LT-94102 - KLAIPEDA - LITHUANIA

Tel. 00370-46-381089 Fax. 00370-445-76466

info@deska.lt

SALES AND TECHNICAL ASSISTANCE SERVICE

All the specifications and images can be subject to variations and upgrades without prior notice.