

ES

"ES" SERIES 4-CELL PLATFORMS, 600x600mm SIZE



Monobloc electronic platforms, fitted with stainless steel bending beam load cells. Suitable for weighing in all types of industrial and commercial applications. Standard version is with approved load cell.

MAIN FEATURES

- Fitted with 4 bending beam, stainless steel, approved load cells with IP68 protection from dust and water.
- Very sturdy monobloc steel tubular structure with fixed sheet-steel chequered loading surface.
- IP68 junction box.
- Oven-fire painted RAL 5007 blue.
- Adjustable, antislip feet and level.
- Up to 15 Vdc power supply.
- Shielded 5m long 6-pin cable with connectors for connection to the indicator.


OPTIONS ONLY AVAILABLE AT TIME OF ORDER

- Connection to the indicator and calibration with CE-M 3000e single range or 3000e+3000e dual range approval.
- Models with special sizes and capacities (ask for estimate).

ACCESSORIES

- Indicator support stand.
- Pit frame for flush floor installation.

DETAIL 1



dimensions in mm

VERSIONS

Versioni disponibili							
	lxwxh	N° celle	Max	d	M	M	d HR
Codice	(mm)	N Cerre	(kg)	(g)	(g)*	2R (g)*	(g)*
ES150-1	600x600x88	4x50kg	150	20	50	20-50	5
ES300-1	600x600x88	4x100kg	300	50	100	50-100	10

^(*) Divisioni ottenibili solo con le relative opzioni, in abbinamento a indicatore di peso Dini Argeo.





DINI ARGEO FRANCE sarl Nogent-sur-Marne

DINI ARGEO **GMBH** Sinsheim - Germany

UK Ltd Taunton - United Kingdom

DINI ARGEO

DINI ARGEO WEIGHING INSTRUMENTS Ltd Shanghai - China

DINI ARGEO WEIGHBRIDGES

Calto (RO) - Italy



HEAD OFFICE Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy







UAB DESKA

KLONALIU K. - ZALGIRIO SEN. - 97144 - KRETINGOS RAJ. LITHUANIA Tel. 00370-46-381089 Fax. 00370-445-76466 info@deska.lt