

SMT

"SMTPLUS": DIRECT AND THERMAL TRANSFER LABELLER



Direct and thermal transfer labeller, connectable to 3590 and CPW indicators. The quick emission of labels, the high printing resolution and the compact size make it suitable for printing in any industrial environment. CE-M approvable.

**The best solution
for advanced industrial
applications**

TECHNICAL FEATURES

- PRINTING METHOD: direct and thermal transfer.
- PRINT RESOLUTION: 8 dots/mm.
- PRINTING SPEED: up to 203 mm/s.
- PRINT MODE: dispensing or strip form.
- MAXIMUM PRINT WIDTH: 108 mm.
- LABEL LENGTH: from 5 mm up to 25400 mm.
- LABEL WIDTH: from 25.4 mm up to 118 mm.
- ROLL SIZE: external diameter up to 203.2 mm.
- THERMAL RIBBON: internal diameter of 25.4 mm, length of 450 metres.
- FONTS: 8, alphanumeric bitmaps, True Type Font.
- USER DISPLAY: 3.5" touchscreen colour HVGA LCD display.
- MEDIA TYPES: die cut labels, tags and continuous strips.
- AVAILABLE BAR CODES:
 - 1D BARCODE: Code 39, Code 93, Code128UCC, Code128 subset A.B.C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN e UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11, China Post.
 - 2D BARCODE: PDF-714, Maxicode, DataMatrix, QR code, Aztec.
- FLASH MEMORY: 128 MB.
- INTERFACES: RS232C (from 1200 to 115200bps) or USB 2.0 client.
- STANDARD SOFTWARE PROGRAMMING, for the creation of customised labels with logos, images, weight data, and bar codes.
- SIZE: 248 x 274 x 436 mm (wxhxl).
- WEIGHT: 9.2 kg.
- POWER SUPPLY: 115/230 Vac, 50/60 Hz.
- OPERATING TEMPERATURE: from +5°C to +40°C.
- OPERATING HUMIDITY: from 25% to 85%, non condensing.

WHAT'S NEW COMPARED TO SMTPLUSPRO:

- Small size and robust design:
 - 39% lighter.
 - 30% less bulky.
- Improved printhead:
 - Adjustable printhead pressure.
 - Reinforced printhead hook.
- 3.5" colour touch screen display.
- 32 times the storage capacity for logos and fonts (128 MB).

DETAIL 1



Simple and quick substitution of the roll.



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO
FRANCE sarl
Nogent-sur-Marne
info.fr@diniargeo.com

DINI ARGEO
GMBH
Sinsheim - Germany
info.de@diniargeo.com

DINI ARGEO
UK Ltd
Taunton - United Kingdom
info.uk@diniargeo.com

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China
info.cn@diniargeo.com

DINI ARGEO
WEIGHBRIDGES
Calto (RO) – Italy
info@diniargeo.com



HEAD OFFICE

Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 843418 Fax. +39.0536 843521
info@diniargeo.com

SERVICE ASSISTANCE

Via Dell'Elettronica, 15
41042 Spezzano di Fiorano Modena - Italy
Tel. +39.0536 921784 Fax. +39.0536 926654
service@diniargeo.com



SALES AND TECHNICAL ASSISTANCE SERVICE